



	A STL inches (cm)	B TTL inches (cm)	C HTL inches (cm)	D HTA	E STA	F CSL inches (cm)	G BBH inches (cm)	H STOOVER inches (cm)	I WB inches (cm)	STACK inches (cm)	REACH inches (cm)
<b>Mach 429SL Carbon 100mm Travel Fork</b>											
S	17.00 (43.18)	23.00 (58.42)	4.00 (10.16)	70.30	72.90	17.65 (44.83)	12.75 (32.38)	27.70 (70.35)	42.89 (108.94)	23.69 (60.17)	15.65 (39.75)
M	18.50 (46.99)	24.00 (60.96)	4.00 (10.16)	70.30	72.90	17.65 (44.83)	12.75 (32.38)	29.30 (74.42)	43.90 (111.50)	23.69 (60.17)	16.67 (42.34)
L	20.00 (50.80)	24.75 (62.87)	4.70 (11.94)	70.30	72.90	17.65 (44.83)	12.75 (32.38)	29.30 (74.42)	44.69 (113.51)	24.37 (61.89)	17.20 (43.68)
XL	22.00 (55.88)	25.60 (65.02)	5.90 (14.99)	70.30	72.90	17.65 (44.83)	12.75 (32.38)	30.50 (77.47)	45.58 (115.77)	25.49 (64.74)	17.70 (44.95)
<b>Mach 429SL Carbon 120mm Travel Fork</b>											
S	17.00 (43.18)	23.00 (58.42)	4.00 (10.16)	69.30	71.90	17.65 (44.83)	13.00 (33.02)	28.00 (71.12)	43.16 (109.63)	23.96 (60.86)	15.24 (38.71)
M	18.50 (46.99)	24.00 (60.96)	4.00 (10.16)	69.30	71.90	17.65 (44.83)	13.00 (33.02)	29.60 (75.18)	44.17 (112.19)	23.96 (60.86)	16.27 (41.33)
L	20.00 (50.80)	24.75 (62.87)	4.70 (11.94)	69.30	71.90	17.65 (44.83)	13.00 (33.02)	29.60 (75.18)	44.96 (114.20)	24.65 (62.61)	16.80 (42.67)
XL	22.00 (55.88)	25.60 (65.02)	5.90 (14.99)	69.30	71.90	17.65 (44.83)	13.00 (33.02)	30.80 (78.23)	45.85 (116.46)	25.77 (65.46)	17.29 (43.92)



2015  
**PIVOT CYCLES**  
**MACH 429 SL**

**MACH 429 SL**

1.877.85.PIVOT [www.pivotcycles.com](http://www.pivotcycles.com)



**duLink** PATENTED WORLD WIDE  
 7048292  
 7128329  
 7828314  
 AU: 2004276314, 2004276310  
 NZ: 545518



1 663 768  
 1 939 084

**Racing is a new game** and the half pound lighter Pivot Mach 429SL Carbon is the bike you need when the course tests both your engine size and handling skills.

The space age chassis drops over 226g via the use of leading-edge carbon fiber and our proprietary hollow-core, internal-molding process. Optimizing the composite materials and lay-up structure in the huge, box-section downtube and bottom bracket area, the tapered head tube and the highly-specific rear triangle tube sections enables us to make this the lightest, stiffest 29er with the best power transfer available.

The Pivot Mach 429SL Carbon is fully Di2 integrated (only from Pivot!). Featuring our innovative Cable Port System, internal routing is easy to install and maintain with large, easy-to-access ports and interchangeable covers for the cleanest installation of wires, batteries and cables. No matter what components or gearing you choose, now or in the future, we have you covered.

Our race-winning, trail-slaying Mach 429SL Carbon geometry is tried, tested and confidence-inspiring. On the uphill, you benefit from the latest in dw-link® suspension design with a Fox Float Kashima Factory shock, performance-tuned specifically for the Mach 429SL Carbon. You can expect World Cup level efficiency provided by dw-link®'s anti-squat characteristics, instant acceleration and unparalleled climbing traction. Downhill, the 100mm of dw-link® suspension performs like a longer travel bike – an incredibly capable ride in technical terrain and ready for record-setting descents.



**Bicycling**  
**EDITORS' CHOICE**  
**2014**

# MACH429<sup>SL</sup>

- 100mm travel dw-link® rear suspension with race and trail tuning
- 1/2lb (226g) weight savings: Frame weight from 5.3lbs (2.4Kg) and Sub 23lb (10.4kg) complete
- Full carbon frame featuring proprietary hollow core internal molding technology
- 29 inch wheels for the fastest laps and best rollover
- Full length internal cable routing and Shimano Di2 integration via Pivot's exclusive, easy-to-maintain Cable Port System
- Full internal dropper post compatible routing
- Cold forged alloy linkages with Enduro Max Cartridge Bearings
- Fox Float Kashima Factory shock, performance tuned for the Mach 429SL
- Highly durable rubberized leather downtube and swingarm protection

*Natural Carbon/Blue  
w/Shimano XTR/XT Pro 1X build*